


LEDDriving HL EASY XEN D3S



Easy plug & play installation

Accurate mechanical compatibility – no adapters and/or caps needed



Compact LED replacement for conventional high and low beam lamps

Same geometry as HID – allowing high compatibility with plenty of car models



Cool White color temperature of 6,500 K

Better visibility thanks to daylight effect



OSRAM's first Plug & Play off-road LED replacement for HID

With extra brightness the OSRAM LEDDriving HL EASY XEN ensures a compact LED replacement of conventional high and low beam lamps. These LED retrofit lamps are 12/24V compatible, come with a color temperature of 6,500 K and ensure a broader light distribution: more light allows to see better and therefore react sooner. The top OSRAM thermal management technology with integrated active cooling – a high speed fan - provides maximized heat dissipation for more powerful performances. Premium OSRAM quality and LED technology grant a long lifetime.

Please note: OSRAM LEDDriving HL EASY XEN change is recommended to be carried out by a professional.

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Technical data

Product information

Product type (off-road vs. on-road)	Off-road ≙ D3S
Application (Category and Product specific)	Mainly used for Low Beam, High Beam

General Product Information

Global order reference	66340DWESY-2HB
------------------------	----------------

Electrical Data

Power input	42.0 W
Nominal voltage	12 V
Nominal wattage	42 W
Test voltage	13.2 V
Power input tolerance	±25 %

Photometric Data

Nominal luminous flux	5000 lm
Luminous flux tolerance	±25 %
Color temperature	6500 K
Light color LED	Cool white

Physical Attributes & Dimensions

Length	71.5 mm
Diameter	13.8 mm
Product weight	75.00 g
Lamp base	PK32d-5

Lifetime Data

Lifespan Tc	5000 hr
-------------	---------

Capabilities

Technology	LED
------------	-----

Environmental & Regulatory Information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Primary article identifier	4062172421461
Candidate list substance 1	No declarable substances contained

Product datasheet

Declaration no. in SCIP database	No declarable substances contained
----------------------------------	------------------------------------

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4062172421461	LEDiving HL EASY XEN ≙ D3S	Hanging Folding Box 2	130 mm x 61 mm x 150 mm	1.19 dm ³	236.00 g
4062172421478	LEDiving HL EASY XEN ≙ D3S	Shipping carton box 8	258 mm x 139 mm x 170 mm	6.10 dm ³	1099.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Download Data

File	
	User instruction GPRS_Safety symbols instructions

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

